

Confidex Leaf RFID Label

Sustainable paper-based and plastic-free UHF RFID label suitable for indirect contact with food. Delivered on reel with water-soluble adhesive for short-term logistics, food shipping and eco-conscious supply chain applications.



RFID SPECIFICATION

Protocol	UHF RFID / EPCglobal Gen2v2 (ISO 18000-6C)
Integrated Circuit	Impinj Monza 4E
Operating Frequency	865–928 MHz (Global)
EPC Memory	496 bit
User Memory	128 bit
TID Memory	96 bit
Read Range – ETSI on cardboard	Up to 8 m / 26 ft
Read Range – FCC on cardboard	Up to 10 m / 33 ft
Applicable Surfaces	Non-metallic surfaces

PHYSICAL SPECIFICATION

Tag Dimensions	92 × 27 mm / 3.62 × 1.06 in
Tag Materials	Paper face material (plastic-free)
Adhesive	Water-soluble adhesive
Delivery Format	2000 pcs on reel
Pitch on Reel	33.87 mm / 1.333 in
Reel Core Inner Diameter	76 mm / 3 in
Minimum Bending Diameter	50 mm

ENVIRONMENTAL RESISTANCE

Application Temperature	0°C to +30°C / 32°F to +86°F
Operating Temperature	-30°C to +55°C / -22°F to +131°F
Storage Condition	6 months shelf life at +20°C / 45% RH (original sealed package)
Additional Notes	Label is sensitive to environmental humidity; store in plastic sealed packages

FEATURE HIGHLIGHTS

- Paper-based and 100% plastic-free – sustainable RFID label
- Suitable for indirect food contact applications
- Impinj Monza 4E IC – 865–928 MHz global operation
- Read range up to 8 m (ETSI) / 10 m (FCC) on cardboard
- Water-soluble adhesive – 92 × 27 mm on 2000 pcs/reel
- Applications: short-term logistics, food shipment tracking

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag