

Confidex Steelwave Classic RFID Tag

Thin all-surface UHF RFID tag for returnable transit item tracking with extreme performance. Delivers read ranges up to 12 m on metal and up to 11 m on other materials in a slim 115 × 30 × 3.9 mm enclosure.



RFID SPECIFICATION

Protocol	EPC Class1 Gen2 ISO 18000-6C / EPCglobal Gen2v2
Integrated Circuit	Impinj Monza 4QT (4E upon request)
Operating Frequency – ETSI	865–869 MHz
Operating Frequency – FCC	902–928 MHz
Memory (Monza 4QT)	EPC 128 bit; User 512 bit; TID 96 bit
EPC Content	Unique number encoded
Read Range – on metal	Up to 12 m / 40 ft
Read Range – other materials	Up to 11 m / 36 ft

PHYSICAL SPECIFICATION

Tag Dimensions	115 × 30 × 3.9 mm / 4.53 × 1.18 × 0.15 in
Tag Materials	High quality engineering plastics
Adhesive	High performance acrylic adhesive (metal and painted metal)
Weight	12 g
Amount in Box	50 tags
Delivery Format	Single

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
Water Resistance	IP68
Washing Resistance	Tolerates industrial washing with standard solvents
Storage Condition	1 year at +20°C / 50% RH (adhesive shelf life)
Chemical Resistance	168h sulfuric acid (10%), motor oil, salt water (10%); 1h NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- All-surface performance – 12 m on metal, 11 m on other materials
- Impinj Monza 4QT IC – EPC 128 bit / User 512 bit
- ETSI 865–869 MHz and FCC 902–928 MHz variants
- IP68 waterproof – industrial washing resistance
- High-performance acrylic adhesive for metal and painted metal
- Printable personalization with cover film protection

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag