

Epozzy UHF Metal RFID Tag

128×30×8 mm

Rugged UHF RFID hard tag in 128×30×8 mm engineering plastic housing for metal asset tracking in heavy industry, oil, gas and mining. IP68-rated with read range up to 10 m and multiple attachment options.



RFID SPECIFICATION

Protocol	ISO/IEC 18000-6C (EPC C1G2)
Integrated Circuit	Impinj Monza R6P
Operating Frequency	860–960 MHz
EPC Memory	128 (96) bit
User Memory	32 (64) bit
Read Range (2W ERP FCC)	10 m

PHYSICAL SPECIFICATION

Dimensions	128 × 30 × 8.5 mm
Material	Engineering plastics
Weight	15.5 g
Installation	3M adhesive, screw, magnet, cable
Package	100 pcs / bag

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
IP Classification	IP68
Humidity	98% non-condensing

FEATURE HIGHLIGHTS

- Impinj Monza R6P – ISO/IEC 18000-6C, 860–960 MHz
- Read range up to 10 m on metal (FCC)
- IP68 – attachment: 3M adhesive, screw, magnet or cable

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag