

Epozzy UHF Metal RFID Tag

136×43×10 mm

High-protection UHF RFID metal tag in 136×43×10 mm engineering plastic housing. Delivers exceptional read range up to 30 m and supports multiple attachment methods for demanding industrial environments.



RFID SPECIFICATION

Protocol	ISO/IEC 18000-6C (EPC C1G2)
IC Options	Impinj Monza 4E / 4QT / 4i
Operating Frequency	860–960 MHz
EPC Memory	496 / 128 / 256 bit
User Memory	128 / 512 / 480 bit
Max Read Range (2W ERP FCC)	30 m

PHYSICAL SPECIFICATION

Dimensions	136 × 43 × 10 mm
Material	Engineering plastics
Weight	47 g
Installation	3M adhesive, screw, magnet, cable
Package	100 pcs / bag

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
IP Classification	IP68

FEATURE HIGHLIGHTS

- Impinj Monza 4E/4QT/4i – ISO/IEC 18000-6C, 860–960 MHz
- Read range up to 30 m on metal (FCC)
- IP68 – attachment: 3M adhesive, screw, magnet or cable

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag