

Epozy Printable On-Metal RFID Label 95×22×1.25 mm

High-performance flexible UHF RFID on-metal label in 95×22×1.25 mm format. Delivers exceptional read ranges up to 12 m on metal and 10 m on plastic, ideal for large-scale metal asset tracking.



RFID SPECIFICATION

Protocol	EPC C1G2 (ISO18000-6C)
Integrated Circuit	Impinj Monza R6-P
Operating Frequency	860–960 MHz
EPC Memory	128 bit
User Memory	32 bit
Read Range – on metal (FCC)	12 m
Read Range – on plastic (FCC)	10 m

PHYSICAL SPECIFICATION

Dimensions	95 × 22 × 1.25 mm (L×W×T)
Material	PET / Aluminum Foil / Foam
Installation	Adhesive
Supported Printers	SATO CL4NX, Zebra ZT410, Postek TX3r
Package	500 pcs / roll, 76.2 mm / 3" reel core

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
IP Classification	IP68 (tested 5h at 1m depth)

FEATURE HIGHLIGHTS

- Impinj Monza R6-P – EPC C1G2 (ISO18000-6C), 860–960 MHz
- Best-in-class read range: 12 m on metal / 10 m on plastic (FCC)
- IP68 – flexible PET/Aluminum/Foam adhesive label

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag