

Omni-ID IQ 800P HT

Large format high temperature synthetic RFID hang tag rated to +230°C. Global frequency with Impinj M730 IC delivering 12 m fixed read range for manufacturing, automotive paint and electronics single-use applications.



RF SPECIFICATION

Radio Protocol	EPC Class 1 Gen2v2
Frequency Range	860–960 MHz (Global)
IC Type (Chip)	Impinj M730
EPC Memory	128 bits
User Memory	0 bits
Unique TID	48 bits
Read Range – Fixed Reader	Up to 12.0 m / 39.4 ft
Read Range – Handheld Reader	Up to 6.0 m / 19.7 ft
Material Compatibility	Plastic

PHYSICAL SPECIFICATION

Size	85 × 55 × 0.49 mm / 3.35 × 2.17 × 0.02 in
Material	High Temperature Synthetic Label
Weight	1.5 g
Attachment	Holes for mechanical attachment
Supply Format	1,020 labels (1 roll)

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-40°C to +85°C
Max Temperature Exposure	-40°C to +230°C
IP Rating	IP68
Shock & Vibration	MIL-STD-810 G
Certifications	CE, RoHS

FEATURE HIGHLIGHTS

- Impinj M730 – EPC Class 1 Gen2v2, 860–960 MHz (Global)
- Exceptional 12 m fixed / 6 m handheld read range
- Survives up to +230°C – IP68, MIL-STD-810 G, 85×55 mm label

PRODUCT GROUP

Category	UHF RFID High Temperature Label
Product Group	RFID Label / Tag