

Xerafy DATA-TRAK-II

Xerafy DATA-TRAK-II is an industrial RFID tag with read range Up to 8.20 ft (2.50 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	860-960 MHz (Global)
Chip	1 Impinj M4QT
Memory	128 bits EPC; 96 bits TID 512 bits user memory
Read Range On Metal	Up to 8.20 ft (2.50 m)
Read Range Off Metal	Up to 5.91 ft (1.80 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	Industry grade polymer
Dimensions (mm)	38 x 13 x 4
Dimensions (in)	1.50 x 0.51 x 0.16
Weight	0.08 oz (2.40 g)
Tethering Hole Diameter	0.10 in

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Compression Strength	14.5 psi (100 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Off metalOn metal, Data centers, IT asset management, Manufacturing WIP, Automated inventory
--------------	--

FEATURE HIGHLIGHTS

- Up to 8.20 ft (2.50 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag