

Xerafy METAL-SKIN-MERCURY

Xerafy METAL-SKIN-MERCURY is an industrial RFID tag with read range Up to 26.25 ft (8 m), IP68 protection.



RFID SPECIFICATION

Protocol	150/IEC 18000-6C (EPC Gen2)
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU) NXP:
Chip	NXP UCODE 9; Impinj Monza R6-P
Memory	96 bits EPC, 96 bits TID; 128 bits EPC; 96 bits TID 32 bits user memory
Write Cycles	100,000 times
Data Retention	20 years; 50 years
Read Range On Metal	Up to 26.25 ft (8 m)
Read Range Off Metal	Up to 19.69 ft (6 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	White thermal transfer face stock NXP:
Dimensions (mm)	101.60 x 38 x 1; 100 x 40 x 1
Dimensions (in)	x 1.50 x 0.04; 3.94 x 1.57 x 0.04
Weight	1.98 lbs (0.90 kg); 2.65 lbs (1.20 kg)
Packing Information	300pcs/roll

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Compression Strength	92 psi (634 kPa)
Vibration	MIL-STD-810G
Storage Humidity	50±15%RH
Printer Compatibility	SATO CL4NX,
Warranty	1 year

FEATURE HIGHLIGHTS

- Up to 26.25 ft (8 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag