

Xerafy ROSWELL

Xerafy ROSWELL is an industrial RFID tag with read range
Up to 16.40 ft (5 m), IP68, IP69K protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	Alien Higgs 9
Memory	96 bits EPC; 96 bits TID 688 bits user memory
Read Range (Fixed)	Up to 16.40 ft (5 m)
Read Range (Handheld)	Up to 11.48 ft (3.50 m)
Polarization	Linear
Radiation Pattern	on metal

PHYSICAL SPECIFICATION

Material	Stainless steel, High- performance engineered polymer
Dimensions (mm)	48 x 28 x 13.50
Dimensions (in)	1.89 x 1.10 x 0.53
Weight	1.55 oz (44 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +250°C -40°F to +482°F
Chemical Resistance	3 24h H2SO4 (10% sulfuric acid) 24h HNO3 (10% nitric acid) 24h H3PO4 (20% phosphoric acid) 24h H2O2 (25% hydrogen peroxide) 24h NaOH (10% sodium hydroxide) ROSWELL Autoclavable
IP Rating	IP68, IP69K
Compression Strength	1145 psi (7900 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Sterilizable surgical trays, Medical devices, Oil & Gas valve/wellhead, management, Food processing plants, Automotive manufacturing
--------------	--

FEATURE HIGHLIGHTS

- Up to 16.40 ft (5 m)
- IP68, IP69K
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag