

Xerafy TEX-50X12

Xerafy TEX-50X12 is an industrial RFID tag with read range
Up to 16.40 ft (5 m); Up to 19.69 ft (6 m).



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	860-960 MHz (Global)
Chip	NXP UCODE 9xe; Impinj M830
Memory	128 bits EPC; 96 bits TID
Write Cycles	100,000 times; 10,000 times
Data Retention	20 years; 10 years
Read Range (Fixed)	Up to 16.40 ft (5 m); Up to 19.69 ft (6 m)
Read Range (Handheld)	Up to 13.12 ft (4 m) Impinj; Up to 26.25 ft (4.80 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	Textile
Dimensions (mm)	50 x 12
Dimensions (in)	1.97 x 0.47
Color	White
Weight	0.30 g

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F Washing: 90°C (194° F), 15 minutes Pre-drying: 180°C (356°F), 30 minutes Ironing: 185°C (365°F), 10 seconds Heat-sealing: 210°C (410°F), 20 seconds Sterilization process: 135°C (275°F), 20 minutes
Vibration	MIL-STD-810G
Storage Humidity	8% - 95% RH
Warranty	200 washing cycles or 3 years

APPLICATIONS

Applications	The chemical resistance is based on the concentration of solutions and application environment. Please contact Xerafy for further details on, Medical scrubs, Hospital linens, Hotel linens, Uniforms, Rental costumes
--------------	--

FEATURE HIGHLIGHTS

- Up to 16.40 ft (5 m); Up to 19.69 ft (6 m)
- -40°C to +85°C -40°F to +185°F Washing: 90°C (194° F), 15 minutes Pre-drying: 180°C (356°F),...
- NXP UCODE 9xe; Impinj M830

PRODUCT GROUP

Category	RFID Laundry Tag
Product Group	RFID Label / Tag