

Xerafy VERSA-TRAK

Xerafy VERSA-TRAK is an industrial RFID tag with read range Up to 29.53 ft (9 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	860-960 MHz (Global)
Chip	Impinj M750
Memory	96 bits EPC; 96 bits TID 32 bits user memory
Write Cycles	10,000 times
Data Retention	10 years
Read Range On Metal	Up to 29.53 ft (9 m)
Read Range Off Metal	Up to 9.84 ft (3 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	Industry grade polymer
Dimensions (mm)	50.30 x 17 x 5.30
Dimensions (in)	1.98 x 0.67 x 0.21
Weight	0.11 oz (3 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Compression Strength	26.1 psi (180 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Returnable transport item (RTI), management, Pallet logistics, Storage rack identification
--------------	--

FEATURE HIGHLIGHTS

- Up to 29.53 ft (9 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag