

# Xerafy XPLORED-SCREW

Xerafy XPLORED-SCREW is an industrial RFID tag with read range Up to 16.40 ft (5 m), IP68, IP69K protection.



## RFID SPECIFICATION

|                       |                                    |
|-----------------------|------------------------------------|
| Protocol              | EPC global Class 1 Gen 2           |
| Operating Frequency   | 902-928 MHz (US); 865-868 MHz (EU) |
| Chip                  | NXP UCODE 9                        |
| Memory                | 96 bits EPC; 96 bits TID           |
| Write Cycles          | 100,000 times                      |
| Data Retention        | 20 years                           |
| Read Range (Fixed)    | Up to 16.40 ft (5 m)               |
| Read Range (Handheld) | Up to 9.84 ft (3 m)                |
| Polarization          | Linear                             |
| Radiation Pattern     | in metal                           |

## PHYSICAL SPECIFICATION

|                 |                                     |
|-----------------|-------------------------------------|
| Material        | High-performance engineered polymer |
| Dimensions (mm) | ø 24 x 10.01, hole: ø 3             |
| Dimensions (in) | ø 0.94 x 0.39, hole: ø 0.12         |
| Weight          | 0.23 oz (6.60 g)                    |

ENVIRONMENTAL RESISTANCE

|                       |                                                                   |
|-----------------------|-------------------------------------------------------------------|
| Operating Temperature | -40°C to +85°C -40°F to +185°F                                    |
| Survival Temperature  | -40°C to +250°C (100 hours) -40°F to +482°F                       |
| Chemical Resistance   | 3 168h H2SO4 (10% sulfuric acid) 168h NaOH (10% sodium hydroxide) |
| IP Rating             | IP68, IP69K                                                       |
| Shock                 | 3 ft (1 m) to concrete/granite                                    |
| Vibration             | MIL-STD-810G                                                      |
| Warranty              | 1 year                                                            |

APPLICATIONS

|              |                                                                                                                                                                                                                               |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applications | output power., The chemical resistance is based on the concentration of solutions and application environment. Please contact Xerafy for further details on, 168h H2SO4 (10% sulfuric acid), 168h NaOH (10% sodium hydroxide) |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

FEATURE HIGHLIGHTS

- Up to 16.40 ft (5 m)
- IP68, IP69K
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

|               |                       |
|---------------|-----------------------|
| Category      | UHF RFID On-Metal Tag |
| Product Group | RFID Label / Tag      |