

SICK RFU630-04100

The SICK RFU630-04100 is a high-performance industrial UHF RFID reader designed for logistics, transport, and manufacturing applications. With 4 external antenna ports, integrated MicroSD card slot, IP67 aluminum housing, and support for industrial protocols including PROFINET, EtherNet/IP, OPC UA, and EtherCAT, it serves automated identification systems in the harshest environments.



FEATURES

Version	Long Range
Product category	Integrated antennaless RFID read/write device
Radio approval	Europe, South Africa, Saudi Arabia, Egypt
Frequency band	UHF (860 MHz ... 960 MHz)
Carrier frequency	865.7 MHz ... 867.5 MHz
Output power	Adjustable up to 30 dBm at external antenna ports
RFID Standard	EPCglobal UHF Class 1 Generation 2, ISO/IEC 18000-6 C
Modulation	PR-ASK, DSB-ASK
Reading range	≤ 10 m (depending on transponder and environment)
Antenna	Not integrated; 4 external antennas (individually adjustable up to +30 dBm)

MECHANICAL / ELECTRICAL

Connection type	1 x M12 17-pin male (A-coded); 1 x M12 4-pin female (D-coded); 1 x USB micro-B
Supply Voltage	18 V DC ... 30 V DC
Power consumption	Typ. 20 W
Housing	Aluminum die-cast
Housing color	Blue, black, silver
Protection class (housing)	IP67
Protection class (electrical)	III
Weight	2.1 kg
Dimensions (L x W x H)	239 mm x 197 mm x 40 mm
MTBF	28 years

INTERFACES

Ethernet	TCP/IP, OPC UA, 10/100 Mbit/s
PROFINET	PROFINET Single Port / Dual Port (CDF600-2 optional), 10/100 Mbit/s
EtherNet/IP	Host, 10/100 Mbit/s
EtherCAT	Via external fieldbus module CDF600
Serial	RS-232, RS-422 (4-wire), 0.3 kBaud ... 115.2 kBaud
CAN	CSN (SICK CAN Sensor Network)
PROFIBUS DP	Via external module CDF600-2
USB	USB 2.0 (AUX)
CANopen	Host
Digital inputs	2 (physical) + 2 logical via CMC600
Digital outputs	2 (physical) + 2 logical via CMC600

USER INTERFACE

Optical indicators	7 multi-color LEDs (device status); 1 RGB-LED (process feedback)
Acoustic indicators	1 buzzer (feedback)
Controls	2 buttons (selection and start/stop)
Operator interface	Web server
Configuration software	SOPAS ET
Programming interface	SICK AppStudio device-specific programming
Memory card	MicroSD (parameter cloning, data logging)

ENVIRONMENTAL DATA

EMC	EN 301489-3, EN 50121-4 (2017)
Vibration resistance	EN 60068-2-64:2008-02
Shock resistance	EN 60068-2-27:2009-05
Operating ambient temperature	-30 °C ... +60 °C
Storage temperature	-30 °C ... +70 °C
Permissible relative humidity	± 90 %, non-condensing

FEATURE HIGHLIGHTS

- Supports EPCglobal UHF Class 1 Generation 2 and ISO/IEC 18000-6 C standards
- Four external antenna ports for flexible coverage
- Integrated MicroSD card slot for parameter cloning and data logging
- Robust IP67-rated aluminum housing for harsh industrial environments
- Supports multiple industrial protocols including PROFINET, EtherNet/IP, and OPC UA
- Programmable via SICK AppStudio for custom logic

PRODUCT GROUP

Category	RFID Reader
Product Group	Industrial Fixed UHF RFID Reader