

Alien ALN-9654 G Label 4x2"

High-performance UHF RFID label in 4x2" TT-printable white wet format, embedding the Alien Higgs-3 inlay. Designed for general-purpose non-metal surface asset tracking and identification.



RFID SPECIFICATION

Protocol	ISO/IEC 18000-6C, EPCglobal Class 1 Gen 2
Integrated Circuit	Alien Higgs-3
Operating Frequency	840–960 MHz
EPC Size	96–480 Bits
User Memory	512 Bits
TID	32 Bits
Unique TID	64 Bits
Access Password	32 Bits
Kill Password	32 Bits

LABEL DIMENSIONS

Label Size	4x2" (103 x 52 mm)
Inlay Width	3.799" [96.5 mm]
Inlay Length	0.913" [23.2 mm]
Web Width	3.925" [99.7 mm]
Web Pitch	1.0" [25.4 mm]
Inlays per Roll	12,500 Nominal
Maximum Roll OD	< 16" [406.4 mm]
Printable Surface	White TT Printable White Film
Overlay Adhesive	General Purpose Permanent
Inlay Adhesive	General Purpose Permanent
Adhesive Application Temp	> +25°F [-4°C]
Adhesive Service Temp	-40°F to +200°F [-40°C to +93.3°C]
Release Liner	40# SCK

ENVIRONMENTAL

Shelf Life	2 years at +25°C @ 40% RH
Recommended Storage	+25°C @ 40% RH
Storage Limits	-25°C to +50°C, 20–90% RH non-condensing
Operating Limits	-40°C to +70°C, 20–90% RH non-condensing
Write Cycles	100,000 @ 25°C
RoHS	2002/95/EC, 2005/618/EC, 2011/65/EU Compliant
REACH	1907/2006/EC Compliant
ESD Limit (HBM / CDM)	5.0 kV / 1.5 kV

FEATURE HIGHLIGHTS

- 4x2" (103 x 52 mm) white thermal-transfer printable label format
- Alien Higgs-3 IC – 840–960 MHz worldwide UHF operation
- 512-bit User Memory and 96–480-bit extensible EPC
- General-purpose permanent adhesive for non-metal surfaces
- Pre-programmed 64-bit Unique TID for serialization and authentication
- Password-protected read/write with 32-bit Access and Kill passwords
- World Tag compliant – consistent operation across all world regions

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Inlay