

Brady B-7425 Special Purpose UHF RFID Label 45×30 mm

45×30 mm polypropylene B-7425 UHF RFID label for laboratory identification on conical tubes and well plates. Up to 6 m read range, 448-bit EPC and 2048-bit user memory. 500 labels per roll.



RFID SPECIFICATION

RFID Type	UHF
Frequency	860–960 MHz
Material (Label)	Polypropylene (B-7425)
EPC Memory	448 bits
User Memory	2048 bits
Read Range	Up to 6 m
On-Metal	No

PHYSICAL SPECIFICATION

Label Reference	THT-UHF-B7425-45x30
Art Number	309082
Dimensions	45×30 mm
Quantity / Roll	500
Operating Temperature	-40°C to +85°C
Markets	General, Laboratory, Manufacturing, Healthcare

FEATURE HIGHLIGHTS

- Polypropylene B-7425 material – laboratory-grade durability
- UHF 860–960 MHz – up to 6 m read range
- Large 448-bit EPC memory + 2048-bit user memory
- 45×30 mm format for conical tubes and well plates
- 500 labels per roll
- Operating temperature -40°C to +85°C
- Fully customisable: antenna, chip, material, adhesive and print

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Inlay