

Confidex Carrier Dual RFID Label

Dual-frequency RFID label combining UHF (860–960 MHz) and HF/NFC (13.56 MHz) in a single slim tag. Ideal for supply chain management, inventory counting and NFC-based mobile interaction.



RFID SPECIFICATION

Protocol	ISO/IEC 18000-63 (UHF) + ISO/IEC 15693 (HF)
Integrated Circuit	EM Microelectronic EM4425
UHF Frequency	860–960 MHz (Global)
HF/NFC Frequency	13.56 MHz
UHF Read Range	Up to 11 m (ETSI)
NFC Read Range (Mobile)	Up to 3 cm
NFC Read Range (Fixed)	Up to 60 cm

PHYSICAL SPECIFICATION

Dimensions	36 × 70 × 0.2 mm
Material	Printable white PET
Adhesive	Permanent acrylic adhesive
Delivery Format	Reel
Applicable Surfaces	Non-metal

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
Chemical Resistance	Salt water, motor oil, sulfuric acid (10%), NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Dual UHF + HF/NFC in one tag – EM Microelectronic EM4425
- UHF read range up to 11 m; NFC mobile read up to 3 cm
- ISO/IEC 18000-63 + ISO/IEC 15693 compliant
- Printable white PET – 36 × 70 × 0.2 mm
- Enables simultaneous long-range UHF and smartphone NFC interaction
- Operating temperature -35°C to +85°C

PRODUCT GROUP

Category	Dual-Frequency RFID Label
Product Group	RFID Label / Tag