

Confidex Crosswave Classic RFID Label

Dual-dipole UHF RFID label with Impinj M730 IC, optimized for plastic and cardboard surfaces. Provides 360-degree read angle and read ranges up to 11 m for logistics and inventory management.



RFID SPECIFICATION

Protocol	EPCglobal UHF Class 1 Gen 2 (ISO 18000-6C)
Integrated Circuit	Impinj M730
Operating Frequency	865–928 MHz (Global)
Read Range (2W ERP)	Up to 11 m on plastic

PHYSICAL SPECIFICATION

Dimensions	75 × 50 × 0.2 mm
Material	Printable matt coated paper
Adhesive	Permanent adhesive
Delivery Format	Reel
Applicable Surfaces	Plastic, cardboard, non-metal

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +70°C / -31°F to +158°F
Chemical Resistance	Salt water, motor oil exposure
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Dual-dipole antenna for 360-degree read angle
- Impinj M730 IC – 865–928 MHz global operation
- Read range up to 11 m on plastic
- 75 × 50 mm printable matt-coated paper label
- Applications: logistics, inventory management, supply chain

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag