

Confidex Cruiser Windshield Crypto RFID Label

Secure UHF RFID windshield label with NXP UCODE DNA cryptographic IC for authenticated vehicle identification. Engineered for high-speed tolling, parking systems and traffic management requiring tamper-proof vehicle authentication.



RFID SPECIFICATION

Protocol	EPCglobal Gen2v2 (ISO 18000-6C)
Integrated Circuit	NXP UCODE DNA
Security	Cryptographic authentication
Operating Frequency	860–960 MHz (Global)
Read Range – ETSI on glass	Up to 10 m / 33 ft
Read Range – FCC on glass	Up to 8 m / 26 ft

PHYSICAL SPECIFICATION

Dimensions	107 × 21.5 × 0.2 mm
Material	Aluminum antenna; transparent PET front
Adhesive	Acrylic adhesive
Delivery Format	Reel
Applicable Surfaces	Glass (windshield)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
UV Resistance	Excellent
Chemical Resistance	Automotive chemicals, salt water
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- NXP UCODE DNA IC with cryptographic authentication
- EPCglobal Gen2v2 – 860–960 MHz global operation
- Read range up to 10 m (ETSI) / 8 m (FCC) on glass
- Tamper-proof authenticated vehicle identification
- 107 × 21.5 mm windshield label format
- Applications: toll collection, parking management, traffic optimization

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag