


Confidex Cruiser Windshield RFID Label

Passive UHF RFID label engineered for vehicle windshields, enabling fast and reliable vehicle identification. Suitable for OGS/HGS toll applications, parking management and vehicle authentication systems.



RFID SPECIFICATION

Protocol	EPCglobal Gen2v2 (ISO 18000-6C)
Integrated Circuit	Impinj Monza 4E
Operating Frequency	860–960 MHz (Global)
Read Range on Glass (ETSI)	Up to 8 m / 26 ft
Read Range on Glass (FCC)	Up to 8 m / 26 ft

PHYSICAL SPECIFICATION

Dimensions	92 × 26 × 0.2 mm
Material	PP back + PP front (printable)
Adhesive	Acrylic adhesive
Delivery Format	Reel
Applicable Surfaces	Glass (windshield)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +70°C / -31°F to +158°F
UV Resistance	Excellent
Chemical Resistance	Automotive chemicals, salt water
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Specifically designed for vehicle windshield attachment
- Impinj Monza 4E IC – EPCglobal Gen2v2
- Read range up to 8 m on glass (ETSI/FCC)
- PP front and back construction for printability
- Applications: OGS/HGS tolling, parking management, vehicle authentication
- 92 × 26 × 0.2 mm format

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag