

Confidex Ferrowave Classic
RFID Label

High-performance all-surface UHF RFID label for metal, liquid, plastic, glass and cardboard. IP68-rated and engineered to deliver reliable performance on metal surfaces with read ranges up to 5 m (FCC).



RFID SPECIFICATION

Protocol	EPCglobal UHF Class 1 Gen 2v2 (ISO 18000-6C)
IC Options	Impinj Monza R6-P / Monza 4E / NXP UCODE 8m
Operating Frequency	865–868 MHz (ETSI) / 902–928 MHz (FCC)
Read Range – ETSI on metal	Up to 4 m / 13 ft
Read Range – FCC on metal	Up to 5 m / 16 ft
Applicable Surfaces	All surfaces (metal, plastic, glass, liquid, cardboard)

PHYSICAL SPECIFICATION

Dimensions	100 × 17 × 1.1 mm
Material	Printable white PET
Adhesive	Permanent acrylic adhesive
Delivery Format	Reel
Applicable Surfaces	Metal, plastic, glass, liquid, cardboard

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
IP Classification	IP68
Chemical Resistance	168h sulfuric acid, motor oil, salt water; 24h NaOH
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Works on all surfaces including metal and liquids
- IC options: Impinj Monza R6-P / Monza 4E / NXP UCODE 8m
- Read range up to 4 m (ETSI) / 5 m (FCC) on metal
- IP68 waterproof with chemical resistance
- 100 × 17 × 1.1 mm printable white PET label
- Applications: asset tracking, logistics, inventory management

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag