

Confidex Ironside Flag RFID Tag

Excellent-performing IP69K-rated UHF RFID flag tag with unique single-screw attachment. Engineered from high-quality thermoplastic elastomer for the most demanding industrial environments, delivering read ranges up to 11 m on metal.



RFID SPECIFICATION

Protocol	UHF RFID / EPCglobal Gen2v2 (ISO 18000-6C)
Integrated Circuit	Impinj Monza 4E
Operating Frequency	865–928 MHz (Global)
EPC Memory	496 bit
User Memory	128 bit
TID Memory	96 bit
EPC Content	Unique number encoded
Read Range – on metal	Up to 11 m / 36 ft
Read Range – on plastic	Up to 4 m / 13 ft

PHYSICAL SPECIFICATION

Tag Dimensions	52.2 × 29 × 14 mm / 2.1 × 1.1 × 0.55 in
Tag Materials	High quality thermoplastic elastomer
Attachment	Single M5 screw or rivet through hole (15 mm from metal edge)
Weight	5.5 g
Amount in Box	500 pcs
Delivery Format	Single

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C / -40°F to +185°F
Peak Temperature	+140°C / +284°F for 10 min
Water Resistance	IP69K
Storage Condition	1 year at +20°C / 50% RH
Chemical Resistance	168h NaOH (10%), sulfuric acid (10%), motor oil, salt water (10%); 2h acetone
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- IP69K rated – highest ingress protection standard
- Impinj Monza 4E IC – EPC 496 bit / User 128 bit
- Read range up to 11 m on metal / 4 m on plastic
- Single-screw attachment with included metallic limiter
- Peak temperature +140°C / +284°F for 10 min
- High-quality thermoplastic elastomer construction

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag