

Epozzy UHF RFID Jewellery Label

Slim 68×13 mm UHF RFID PET adhesive label for jewellery, watch, glasses and bag tracking. NXP UCode 8 IC with read range up to 8 m (FCC), designed for retail inventory, anti-counterfeiting and warehouse management.



RFID SPECIFICATION

Protocol	EPC C1G2 (ISO18000-6C)
Integrated Circuit	NXP UCode 8
Operating Frequency	860–960 MHz
EPC Memory	128 bit
TID Memory	96 bit
User Memory	32 bit
Read Range – FCC (2W ERP)	8 m
Read Range – ETSI (2W ERP)	3.5 m

PHYSICAL SPECIFICATION

Dimensions	68 × 13 mm
Material	PET
Installation	Adhesive
Customization	Logo, barcode / QR code, number printing

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
IP Classification	IP68

FEATURE HIGHLIGHTS

- NXP UCode 8 – EPC C1G2 (ISO18000-6C), 860–960 MHz
- Read range: 8 m (FCC) / 3.5 m (ETSI)
- IP68 – slim 68×13 mm PET label, optimized for metallic-coated items

PRODUCT GROUP

Category	UHF RFID Jewellery Label
Product Group	RFID Label / Tag