

Epozzy Printable On-Metal RFID Label 55×15×1.25 mm

Ultra-slim flexible UHF RFID on-metal label in 55×15×1.25 mm format. Printable with Sato and Zebra RFID printers, optimized for curved metallic surfaces with read range up to 5.5 m on metal.



RFID SPECIFICATION

Protocol	EPC C1G2 (ISO18000-6C)
Integrated Circuit	Impinj Monza R6-P
Operating Frequency	860–960 MHz
EPC Memory	128 bit
User Memory	32 bit
Read Range – on metal (FCC)	5.5 m
Read Range – on plastic (FCC)	2.8 m

PHYSICAL SPECIFICATION

Dimensions	55 × 15 × 1.25 mm (L×W×T)
Material	PET / Aluminum Foil / Foam
Installation	Adhesive
Supported Printers	SATO CL4NX, Zebra ZT410, Postek TX3r
Package	500 pcs / roll, 76.2 mm / 3" reel core

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
IP Classification	IP68 (tested 5h at 1m depth)

FEATURE HIGHLIGHTS

- Impinj Monza R6-P – EPC C1G2 (ISO18000-6C), 860–960 MHz
- Read range up to 5.5 m on metal / 2.8 m on plastic (FCC)
- IP68 – flexible PET/Aluminum/Foam construction for curved surfaces

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag