

Epozzy UHF PCB On-Metal
RFID Tag 36×13×2.7 mm

Rugged FR-4 PCB on-metal RFID tag in compact 36×13×2.7 mm format. IP68-rated with read range up to 8.5 m on metal, attachable via 3M adhesive or screws. Laser-printable surface for visual identification.



RFID SPECIFICATION

Protocol	ISO/IEC 18000-6 Type-C (EPC Gen2)
Integrated Circuit	NXP UCode 7
Operating Frequency	860–960 MHz
EPC Memory	128 bit
TID Memory	96 bit
User Memory	32 bit
Read Range (2W ERP FCC)	8.5 m on metal

PHYSICAL SPECIFICATION

Dimensions	36 × 13 × 2.7 mm (L×W×T)
Material	FR-4
Installation	3M adhesive or screw
Customization	Logo, serial number, barcode laser printing
Package	200 pcs / bag

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
IP Classification	IP68
Designed Lifetime	Over 5 years in outdoor conditions

FEATURE HIGHLIGHTS

- NXP UCode 7 – ISO/IEC 18000-6 Type-C (EPC Gen2)
- Read range up to 8.5 m on metal (FCC)
- IP68 – FR-4 PCB, attachable by 3M adhesive or screw, laser-printable

PRODUCT GROUP

Category	UHF RFID PCB Tag
Product Group	RFID Label / Tag