

Epozzy UHF RFID Label 4×2 Inch

Passive UHF RFID label in standard 4×2 inch (101×51 mm) format with NXP UCode 8 IC. Performs on both metal and non-metal surfaces including cardboard, plastic and wood.



RFID SPECIFICATION

Protocol	EPC C1G2 (ISO18000-6C)
Integrated Circuit	NXP UCode 8
Operating Frequency	860–960 MHz
Read Range – on metal (ETSI)	Up to 4 m
Read Range – off metal (FCC)	Up to 4.5 m
Applicable Surfaces	Metal, plastic, cardboard, wood

PHYSICAL SPECIFICATION

Dimensions	101.6 × 50.8 mm (4×2 in)
Material	PET / Aluminum Foil / Foam
Installation	Adhesive

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
IP Classification	IP68

FEATURE HIGHLIGHTS

- NXP UCode 8 – EPC C1G2 (ISO18000-6C), 860–960 MHz
- Read range up to 4 m on metal (ETSI) / 4.5 m off-metal (FCC)
- IP68 – standard 4×2 inch format, works on metal and non-metal

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag