

Omni-ID Adept 400 (5-Layer) GS

Rugged 5-layer stainless steel UHF RFID tag for attachment to pipes and fixed assets in remote production, extraction and processing facilities. Global frequency, MIL-STD-810 G rated with optional ATEX/IECEX certification.



RF SPECIFICATION

Radio Protocol	EPC Class 1 Gen2v2
Frequency Range	860–930 MHz (GS)
IC Type (Chip)	Impinj Monza 4QT
EPC Memory	128 bits
User Memory	512 bits
Unique TID	48 bits
Read Range – Fixed Reader	Up to 4 m / 13.1 ft
Read Range – Handheld Reader	Up to 2 m / 6.5 ft
Optimized For	Metal

PHYSICAL SPECIFICATION

Size	45 × 30.5 × 15.5 mm / 1.77 × 1.20 × 0.61 in
Material	Stainless steel with ceramic core
Layers	5 layers
Weight	94 g
Attachment	Steel strap or welded

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-20°C to +65°C
IP Rating	IP68
Shock & Vibration	MIL-STD-810 G
Certifications	CE, RoHS; optional ATEX/IECEX, US&Canada C1D1/D2

FEATURE HIGHLIGHTS

- Impinj Monza 4QT – EPC Class 1 Gen2v2, 860–930 MHz (GS)
- Read range: 4 m fixed / 2 m handheld – optimized for metal
- MIL-STD-810 G, IP68 – steel strap or weld attachment, ATEX option

PRODUCT GROUP

Category	UHF RFID Industrial Tag
Product Group	RFID Label / Tag