

Omni-ID Adept 500 GS

Small circular UHF hard tag designed for permanent attachment to the shoulder of industrial gas cylinders and beverage kegs. Global frequency, Monza R6-P IC with exceptional 12 m fixed read range.



RF SPECIFICATION

Radio Protocol	EPC Class 1 Gen2v2
Frequency Range	860–930 MHz (GS)
IC Type (Chip)	Impinj Monza R6-P
EPC Memory	128 (96) bits
User Memory	32 (64) bits
Unique TID	48 bits
Read Range – Fixed Reader	Up to 12.0 m / 39.4 ft
Read Range – Handheld Reader	Up to 5 m / 16.4 ft
Material Compatibility	Metal

PHYSICAL SPECIFICATION

Size	37 × 37 × 11.5 mm / 1.46 × 1.46 × 0.45 in
Material	Durable thermoplastic material
Weight	9.8 g
Attachment	Adhesive (standard)

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-20°C to +65°C
Short Term Max Temperature	+75°C
IP Rating	IP68
Shock & Vibration	MIL-STD-810 F
Certifications	CE, RoHS; optional ATEX/IECEX, US&Canada C1D1/D2

FEATURE HIGHLIGHTS

- Impinj Monza R6-P – EPC Class 1 Gen2v2, 860–930 MHz (GS)
- Read range: 12 m fixed / 5 m handheld – optimized for metal
- IP68, MIL-STD-810 F – circular 37×37 mm, adhesive attachment

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag