

Omni-ID Exo 400 HT

Small form factor High Temperature UHF RFID tag optimized for metal, withstanding cycling temperatures up to +235°C. Ideal for healthcare sterilization, manufacturing and automotive paint processes.



RF SPECIFICATION

Radio Protocol	EPC Class 1 Gen2v2
Frequency Range – EU	866–868 MHz
Frequency Range – US	902–928 MHz
IC Type (Chip)	Alien Higgs 3
EPC Memory	96 bits
User Memory	512 bits
Unique TID	64 bits
Read Range – Fixed Reader	Up to 4 m / 13.1 ft
Read Range – Handheld Reader	Up to 2 m / 6.5 ft
Material Compatibility	Metal

PHYSICAL SPECIFICATION

Size	37 × 14 × 7.5 mm / 1.46 × 0.55 × 0.30 in
Material	Thermoplastic cover
Weight	5.7 g
Attachment	Mechanical (2 × 3mm holes, standard)

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-20°C to +85°C
Max Temperature Exposure	-20°C to +235°C
IP Rating	IP68
Shock & Vibration	MIL-STD-810 G
Certifications	CE, RoHS; optional ATEX/IECEX, US&Canada C1D1/D2

FEATURE HIGHLIGHTS

- Alien Higgs 3 – EPC Class 1 Gen2v2, EU 866–868 MHz / US 902–928 MHz
- Survives cycling up to +235°C – read range 4 m fixed / 2 m handheld
- IP68, MIL-STD-810 G – 37×14×7.5 mm, mechanical attachment (2×3mm holes)

PRODUCT GROUP

Category	UHF RFID High Temperature Tag
Product Group	RFID Label / Tag