

Omni-ID IQ 400P HT

High temperature synthetic RFID hang tag rated to +230°C for single-use manufacturing applications. Global frequency with Alien Higgs 3 IC, optimized for thermal barcode printing in automotive paint and electronics processes.



RF SPECIFICATION

Radio Protocol	EPC Class 1 Gen2v2
Frequency Range	860–960 MHz (Global)
IC Type (Chip)	Alien Higgs 3
EPC Memory	96 bits
User Memory	512 bits
Unique TID	64 bits
Read Range – Fixed Reader	Up to 4 m / 13.1 ft
Read Range – Handheld Reader	Up to 2 m / 6.5 ft
Material Compatibility	Plastic and non-metallic substrates

PHYSICAL SPECIFICATION

Size	50 × 30 × 0.49 mm / 1.97 × 1.18 × 0.02 in
Material	High Temperature Synthetic Label
Weight	0.51 g
Attachment	Holes for mechanical attachment
Supply Format	1 roll (1,020 labels)

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-40°C to +85°C
Max Temperature Exposure	-40°C to +230°C
IP Rating	IP68
Certifications	CE, RoHS, Ex; optional ATEX/IECEX

FEATURE HIGHLIGHTS

- Alien Higgs 3 – EPC Class 1 Gen2v2, 860–960 MHz (Global)
- Survives up to +230°C – read range 4 m fixed / 2 m handheld
- IP68 – 50×30×0.49 mm synthetic label, CE, RoHS, Ex certified

PRODUCT GROUP

Category	UHF RFID High Temperature Label
Product Group	RFID Label / Tag