

Omni-ID Adept 400 (5-Layer) US

Rugged 5-layer stainless steel UHF RFID tag for pipes and fixed assets in harsh industrial facilities. US band (902–928 MHz) with Alien Higgs 3 IC, MIL-STD-810 G and optional ATEX/IECEx certification.



RF SPECIFICATION

Radio Protocol	EPC Class 1 Gen2v2
Frequency Range	902–928 MHz (US)
IC Type (Chip)	Alien Higgs 3
EPC Memory	96 bits
User Memory	512 bits
Unique TID	64 bits
Read Range – Fixed Reader	4–6 m / 13–20 ft
Read Range – Handheld Reader	1–3 m / 10 ft
Optimized For	Metal

PHYSICAL SPECIFICATION

Size	36 × 25 × 13.5 mm / 1.42 × 0.98 × 0.53 in
Material	Stainless steel with ceramic core
Layers	5 layers
Weight	58 g
Attachment	Steel strap or welded

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-20°C to +65°C
IP Rating	IP68
Shock & Vibration	MIL-STD-810 G
Certifications	CE, RoHS; optional ATEX/IECEX, US&Canada C1D1/D2

FEATURE HIGHLIGHTS

- Alien Higgs 3 – EPC Class 1 Gen2v2, 902–928 MHz (US)
- Read range: 4–6 m fixed / 1–3 m handheld – optimized for metal
- MIL-STD-810 G, IP68 – steel strap or weld attachment, ATEX option

PRODUCT GROUP

Category	UHF RFID Industrial Tag
Product Group	RFID Label / Tag