

# Xerafy CONTAINER-OUTDOOR

Xerafy CONTAINER-OUTDOOR is an industrial RFID tag with read range Up to 131.23 ft (40 m), IP68 protection.



## RFID SPECIFICATION

|                      |                                    |
|----------------------|------------------------------------|
| Protocol             | EPC global Class 1 Gen 2           |
| Operating Frequency  | 902-928 MHz (US); 865-868 MHz (EU) |
| Chip                 | 1 Impinj M830                      |
| Memory               | 128 bits EPC; 96 bits TID          |
| Write Cycles         | 10,000 times                       |
| Data Retention       | 10 years                           |
| Read Range On Metal  | Up to 131.23 ft (40 m)             |
| Read Range Off Metal | Up to 82.02 ft (25 m)              |
| Polarization         | Linear                             |

## PHYSICAL SPECIFICATION

|                 |                        |
|-----------------|------------------------|
| Material        | Industry grade polymer |
| Dimensions (mm) | 139 x 42.20 x 12       |
| Dimensions (in) | 5.46 x 1.65 x 0.47     |
| Weight          | 1.76 oz (50 g)         |

ENVIRONMENTAL RESISTANCE

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Operating Temperature | -40°C to +85°C -40°F to +185°F                              |
| Survival Temperature  | -40°C to +85°C (48 hours) -40°F to +185°F Container OUTDOOR |
| IP Rating             | IP68                                                        |
| Compression Strength  | 29 psi (200 kPa)                                            |
| Shock                 | 3 ft (1 m) to concrete/granite                              |
| Vibration             | MIL-STD-810G                                                |
| Warranty              | 1 year                                                      |

APPLICATIONS

|              |                                                                                                                   |
|--------------|-------------------------------------------------------------------------------------------------------------------|
| Applications | Last-Mile logistics, Supply chain & inventory, management, Returnable transport packaging, (RTP), Yard management |
|--------------|-------------------------------------------------------------------------------------------------------------------|

FEATURE HIGHLIGHTS

- Up to 131.23 ft (40 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

|               |                       |
|---------------|-----------------------|
| Category      | UHF RFID On-Metal Tag |
| Product Group | RFID Label / Tag      |