

Xerafy RTI-OUTDOOR

Xerafy RTI-OUTDOOR is an industrial RFID tag with read range Up to 32.81 ft (10 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	1 NXP U9xe
Memory	128 bits EPC; 96 bits TID
Write Cycles	100,000 times
Data Retention	20 years
Read Range On Metal	Up to 32.81 ft (10 m)
Read Range Off Metal	Up to 26.25 ft (8 m)
Polarization	Linear

PHYSICAL SPECIFICATION

Material	Anti-UV industry grade polymer
Dimensions (mm)	73.30 x 22.80 x 8.65
Dimensions (in)	2.88 x 0.90 x 0.34
Weight	0.39 oz (11 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C (48 hours) -40°F to +185°F
IP Rating	IP68
Compression Strength	26 psi (180 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Up to 32.81 ft (10 m), RTI management, LPG and gas cylinder, Production logistics, Yard management, Long-distance shipping
--------------	--

FEATURE HIGHLIGHTS

- Up to 32.81 ft (10 m)
- IP68
- 40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag