

Xerafy XENSE-STRAIN

Xerafy XENSE-STRAIN is an industrial RFID tag with read range Up to 4.92 ft (1.5 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	Asygn AS3213S
Memory	192 bits EPC; 16 bits TID 96 bits user memory
Read Range (Fixed)	Up to 4.92 ft (1.5 m)
Read Range (Handheld)	Up to 3.28 ft (1 m) In concrete4 Up to 6.56 ft (2 m)
Polarization	Linear
Radiation Pattern	on metal
Sensing Features	-40°C to +120°C
Accuracy	± 1°C

PHYSICAL SPECIFICATION

Material	Industry grade polymer
Dimensions (mm)	131.60 x 30.80 x 7.50
Dimensions (in)	5.18 x 1.21 x 0.30
Weight	1.48 oz (42 g)
Rivet Hole Diameter	0.165 in +/-0.008

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +120°C -40°F to +248°F
IP Rating	IP68
Compression Strength	8,700psi (60MPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	On metal
--------------	----------

FEATURE HIGHLIGHTS

- Up to 4.92 ft (1.5 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag