

Xerafy XS-DOT

Xerafy XS-DOT is an industrial RFID tag with read range Up to 13.12 ft (4 m) US Up to 9.84 ft (3 m) EU, IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902–928 MHz (US); 865–868 MHz (EU)
Chip	NXP UCODE 9xm
Memory	128/496 bits EPC, 96 bits TID, 752/384 bits user memory
Write Cycles	100,000 times
Data Retention	20 years
Read Range (Fixed)	Up to 13.12 ft (4 m) US Up to 9.84 ft (3 m) EU
Polarization	Linear
Radiation Pattern	on metal

PHYSICAL SPECIFICATION

Material	Ceramic
Dimensions (mm)	ø 6 x 2.50
Dimensions (in)	ø 0.24 x 0.10
Weight	0.012 oz (0.34 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
Survival Temperature	-40°C to +150°C (168 hours)
Peak Temperature	200°C (minutes)
IP Rating	IP68
Compression Strength	790 psi (5,447 kPa)
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Hand tools and equipments, MRO tool control, Weapon management
--------------	--

FEATURE HIGHLIGHTS

- Up to 13.12 ft (4 m) US Up to 9.84 ft (3 m) EU
- IP68
- 40°C to +85°C

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag