

Xerafy XS-WEDGE

Xerafy XS-WEDGE is an industrial RFID tag with read range
Up to 4.59 ft (1.40 m) US Up to 3.28 ft (1 m) EU, IP68
protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	1 NXP UCODE 9xm
Memory	128/496 bits EPC, 96 bits TID, 752/384 bits user memory
Read Range (Fixed)	Up to 4.59 ft (1.40 m) US Up to 3.28 ft (1 m) EU
Polarization	Linear; direction is parallel with the; direction forms an angle with
Radiation Pattern	in metal

PHYSICAL SPECIFICATION

Material	Industry grade polymer
Dimensions (mm)	ø 10.30x 4.60
Dimensions (in)	ø 0.41 x 0.18
Weight	0.28 oz (8 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
Survival Temperature	-50°C to +220°C (168 hours)
Peak Temperature	250°C (2 hours)
Chemical Resistance	3 24h H2SO4 (10% sulfuric acid) 24h HNO3 (10% nitric acid) 24h H3PO4 (20% phosphoric acid) 24h H2O2 (25% hydrogen peroxide) 24h NaOH (10% sodium hydroxide)
IP Rating	IP68
Compression Strength	10,100 psi (70 MPa)
Warranty	1 year

APPLICATIONS

Applications	Up to 4.59 ft (1.40 m) US, Up to 3.28 ft (1 m) EU, Onshore and offshore pipes, Heavy equipment and tools, Automotive manufacturing, Industrial molds
--------------	--

FEATURE HIGHLIGHTS

- Up to 4.59 ft (1.40 m) US Up to 3.28 ft (1 m) EU
- IP68
- 40°C to +85°C

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag