

Xerafy XSKIN-GAMMA

Xerafy XSKIN-GAMMA is an industrial RFID tag with read range Up to 52.49 ft (16 m), US Up to 19.68 ft (6 m), EU.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	860-960 MHz (Global)
Chip	Kiloway
Memory	128 bits EPC (configurable from 96 to 240 bits), 96 bits TID, 1312 bits User Memory
Read Range (Fixed)	Up to 52.49 ft (16 m), US Up to 19.68 ft (6 m), EU
Read Range (Handheld)	Up to 31.50 ft (9.60 m), US Up to 8.20 ft (2.50 m), EU
Polarization	Linear
Radiation Pattern	off metal

PHYSICAL SPECIFICATION

Material	Printable white paper
Dimensions (mm)	73 x 20 x 0.16
Dimensions (in)	2.87 x 0.79 x 0.01
Reel Core	: Cardboard

ENVIRONMENTAL RESISTANCE

Operating Temperature	10°C to +40°C
Survival Temperature	-40°C to +85°C
Vibration	MIL-STD-810G
Printer Compatibility	Zebra ZD500R, ZT600

Warranty	1 year
----------	--------

APPLICATIONS

Applications

supplies, Pharmaceuticals and cold-chain, Food processing, Mining and assaying operations, Industrial components and material, inspections

FEATURE HIGHLIGHTS

- Up to 52.49 ft (16 m), US Up to 19.68 ft (6 m), EU
- 10°C to +40°C
- Kiloway

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag