

Brady HH83 UHF RFID Handheld Terminal ACD LTE (2D Imager)

The Brady HH83 UHF RFID Handheld Terminal ACD LTE is a ruggedized handheld RFID scanner featuring a dipole antenna for extended read range, integrated 2D imaging, and 4G LTE connectivity for uninterrupted field operations in challenging industrial environments.



UHF RFID

Air Interface Protocol	EPC Class 1 Gen2v2 (ISO 18000-63)
Operating Frequency	ETSI 865.6–867.6 MHz / FCC/IC 902–928 MHz
Max Receive Sensitivity	-80 dBm
Typical Reading Speed	Up to 1000 tags per second
Antenna Type	Software controllable antenna polarisations (vertical, horizontal or vertical/horizontal switching)
Reader Module	Nordic ID NUR2-1W

PLATFORM

CPU	Octa-Core ARM Cortex-A53 1.8 GHz
Operating System	Android 10
RAM	2 GB
Storage	16 GB Flash
Expansion	MicroSD slot with SDXC support

CAMERA & IMAGER

Camera	5 Mpix rear-facing with autofocus and LED flash (torch mode supported)
Barcode Imager	Integrated 2D imager

CONNECTIVITY

WWAN	4G LTE, 3G, GPRS/EDGE
WLAN	IEEE 802.11 a/b/g/n/ac
Bluetooth	Bluetooth 4.2
USB	USB 2.0 via USB Type-C connector

BATTERY

Battery Type	Rechargeable Lithium-ion
Hot-Swap	Supported

MECHANICAL

Dimensions	(W) 78 mm x (H) 177 mm x (D) 35 mm
Weight	340 g
IP Rating	IP65
Sensors	Accelerometer, ambient light sensor, Time of Flight sensor, proximity sensor, pedometer, gyroscope

ENVIRONMENT

Operating Temperature	-20 °C to +55 °C
-----------------------	------------------

FEATURE HIGHLIGHTS

- Rugged IP65 rated design with drop and impact resistance
- Extended read range with di-pole antenna
- 4G LTE connectivity for seamless field operations
- Hot-swappable battery for continuous operation
- Integrated UHF, HF, NFC and 2D barcode scanning

PRODUCT GROUP

Category	RFID Reader
Product Group	UHF RFID Handheld Terminal