

Avery Dennison AD-183 U9 UHF RFID Inlay

Compact round Ø 26 mm Gen2 UHF RFID inlay with NXP UCODE 9. Achieves class-leading read distances on a wide array of surfaces. Ideal for apparel, cosmetics and personal care product tagging.



RFID SPECIFICATION

Chip	NXP UCODE 9
Standard	ISO/IEC 18000-63 Type C
Frequency Band	UHF 860–960 MHz
EPC Memory	96-bit
TID Memory	96-bit / 48-bit unique serial number
On-Metal	Non metal
Certificate	ARC (RFID Lab, Auburn University)
RoHS	EU Directive 2011/65/EU and Directive (EU) 2015/863
REACH	Regulation (EC) No. 1907/2006

PHYSICAL SPECIFICATION

Antenna Dimensions	Ø 26 mm / 1.02 in
Die-Cut Dimension	29.25 mm / 1.152 in
Dry Inlay (RF602211 / IL-605984)	Opaque PET + 1.2 mil PET overlamine — 9,958 pcs/reel
Wet Inlay (RF602212 / IL-605630)	Opaque PET — 3,341 pcs/reel
Label Paper (RF100993 / IL-606134)	Paper + TT2C face stock — 2,366 pcs/reel
Label PET (RF100994 / IL-612867)	Opaque PET + 1.2 mil overlamine + TC PET — 2,500 pcs/reel
Web Width	36 mm / 1.4 in
Operating Temperature	-40°C to +85°C

FEATURE HIGHLIGHTS

- NXP UCODE 9 chip with 96-bit EPC memory and unique serialized TID
- Compact round Ø 26 mm form factor for small cosmetic items
- Class-leading read distances across diverse surface materials
- Excellent broadband performance 860–930 MHz global design
- Available in dry inlay, wet inlay and paper label formats
- RoHS and REACH compliant
- ARC accredited quality by RFID Lab at Auburn University

PRODUCT GROUP

Category	UHF RFID Inlay
Product Group	RFID Label / Inlay