

altis teknoloji

pursuing perfection with you

Avery Dennison AD-23x U9 Slim UHF RFID Inlay

Slim-profile 70 × 10.5 mm Gen2 UHF RFID inlay with NXP UCODE 9 and Strap Attach. Optimized for supply chain, apparel and brand protection with a narrower footprint than the standard AD-23x for tighter label applications.



RFID SPECIFICATION

Chip	NXP UCODE 9
IC Attachment Technology	Strap Attach
Standard	ISO/IEC 18000-63 Type C
Frequency Band	UHF 860–960 MHz
EPC Memory	96-bit
TID Memory	96-bit / 48-bit unique serial number
On-Metal	Non metal
Certificate	ARC Specification Guide
RoHS	EU Directive 2011/65/EU and 2015/863 Compliant

PHYSICAL SPECIFICATION

Antenna Dimensions	70 × 10.5 mm / 2.756 × 0.413 in
Die-Cut Dimension	73 × 13.5 mm / 2.874 × 0.532 in
Wet Inlay (IL-611239)	40# Paper — pitch 15.88 mm — MAX OD 13"
Label (IL-611588)	40# Paper + TT2C Bright White — pitch 19.05 mm — MAX OD 8"
Web Width	82.55 mm / 3.25 in
Core Size	76 mm / 3 in
Operating Temperature	-40°C to +85°C

FEATURE HIGHLIGHTS

- NXP UCODE 9 with Strap Attach – 96-bit EPC and 96-bit TID
- Slimmer 70 × 10.5 mm antenna vs. standard AD-23x (narrower profile)
- Die-cut 73 × 13.5 mm for wet inlay and label formats
- Available in wet inlay and pressure sensitive label formats
- ARC Specification Guide certified
- RoHS compliant – EU Directive 2011/65/EU and 2015/863

PRODUCT GROUP

Category	UHF RFID Inlay
Product Group	RFID Label / Inlay