

Brady B-7425 Special Purpose UHF RFID Label 53×26 mm

53×26 mm polypropylene B-7425 UHF RFID label for laboratory sample identification, test tubes and pharmaceutical tracking. Up to 10 m read range with 128-bit EPC memory. 500 labels per roll.



RFID SPECIFICATION

RFID Type	UHF
Frequency	860–960 MHz
Material (Label)	Polypropylene (B-7425)
EPC Memory	128 bits
User Memory	—
Read Range	Up to 10 m
On-Metal	Yes (both surfaces)

PHYSICAL SPECIFICATION

Label Reference	THT-UHF-B7425-53x26
Art Number	309081
Dimensions	53×26 mm
Quantity / Roll	500
Operating Temperature	-40°C to +85°C
Markets	General, Laboratory, Manufacturing, Healthcare, Transport & Logistics

FEATURE HIGHLIGHTS

- Polypropylene B-7425 material – chemical and laboratory grade
- UHF 860–960 MHz – up to 10 m read range
- 128-bit EPC memory
- 53×26 mm format for test tubes and specimen containers
- 500 labels per roll
- Operating temperature -40°C to +85°C
- Fully customisable: antenna, chip, material, adhesive and print

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Inlay