

Confidex Carrier Classic RFID Label

Slim printable UHF RFID label optimized for washable plastic surfaces. Engineered for returnable transport items, plastic containers and assets with limited labeling space, delivering read ranges up to 10 m on plastic.



RFID SPECIFICATION

Protocol	EPCglobal UHF Class 1 Gen 2v2 (ISO 18000-6C)
Integrated Circuit	Impinj Monza 4QT
Operating Frequency	860–960 MHz (Global)
Memory	EPC 128 bit; User 512 bit; TID 96 bit
EPC Content	Unique number encoded
Read Range (2W ERP)	Up to 10 m on plastic (ETSI)

PHYSICAL SPECIFICATION

Dimensions	73 × 8 × 0.2 mm
Material	Printable white PET
Adhesive	Permanent acrylic adhesive
Delivery Format	Reel
Applicable Surfaces	Plastic, non-metal

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
IP Classification	IP68
Washing Resistance	Industrial laundry up to 60°C
Chemical Resistance	Salt water, motor oil, sulfuric acid (10%), NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- EPCglobal Gen2v2 – 860–960 MHz global operation
- Impinj Monza 4QT IC with 512-bit User Memory
- Read range up to 10 m on plastic (ETSI)
- IP68 waterproof – withstands industrial washing up to 60°C

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag