

Confidex Carrier Pro RFID Label

High-performance washable UHF RFID label optimized for low surface energy plastics and returnable transport items (RTI). Delivers read ranges up to 12.5 m on plastic and withstands industrial wash cycles.



RFID SPECIFICATION

Protocol	EPCGlobal Class1 Gen2 ISO 18000-6C
IC Options	Impinj Monza 4QT / Monza 4E
Operating Frequency	860–960 MHz (Global)
Memory (Monza 4QT)	EPC 128 bit; User 512 bit; TID 96 bit
Memory (Monza 4E)	EPC 496 bit; User 128 bit; TID 96 bit
Read Range (2W ERP)	Up to 12.5 m on plastic (ETSI)

PHYSICAL SPECIFICATION

Dimensions	92 × 24 × 0.2 mm
Material	Printable white PET
Adhesive	Permanent acrylic adhesive
Delivery Format	Reel
Applicable Surfaces	Plastic, LSE plastics, non-metal

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
IP Classification	IP68
Washing Resistance	Industrial laundry up to 60°C
Chemical Resistance	Salt water, motor oil, sulfuric acid (10%), NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Optimized for low surface energy (LSE) plastics and RTI
- Impinj Monza 4QT / 4E IC options
- Read range up to 12.5 m on plastic (ETSI)
- IP68 waterproof – withstands industrial washing

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag