

Confidex Crosswave Neo RFID Label

High-performance printable UHF RFID label with Impinj M730 IC and 360-degree read capability. Designed for logistics, asset tracking and washable plastic surface applications requiring excellent read range.



RFID SPECIFICATION

Protocol	EPCglobal UHF Class 1 Gen 2 (ISO 18000-6C)
Integrated Circuit	Impinj M730
Operating Frequency	865–928 MHz (Global)
Read Range (2W ERP)	Up to 11 m on plastic

PHYSICAL SPECIFICATION

Dimensions	75 × 50 × 0.2 mm
Material	Printable matt coated paper
Adhesive	Permanent adhesive
Delivery Format	Reel
Applicable Surfaces	Plastic, non-metal

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +70°C / -31°F to +158°F
Chemical Resistance	Salt water, motor oil exposure
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Impinj M730 IC – 865–928 MHz global operation
- 360-degree read angle for omnidirectional scanning
- Read range up to 11 m on plastic
- 75 × 50 mm printable matt-coated paper label
- Applications: logistics, asset tracking, washable plastic surfaces

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag