

Confidex Heatwave Flag RFID Tag

High-temperature resistant UHF RFID flag tag engineered for automotive paint shop processes. Withstands peak temperatures up to 260°C for 10 minutes and attaches via Ø5 mm screw or rivet holes, surviving the full paint shop lifecycle.



RFID SPECIFICATION

Protocol	UHF RFID / EPCglobal Gen2v2
Integrated Circuit	Alien Higgs 9
Operating Frequency	865–928 MHz (Global)
EPC Memory	96 bit (extendable to 496 bit)
User Memory	688 bit
TID Memory	96 bit
EPC Content	Unique number encoded
Read Range (2W ERP)	Up to 10 m / 33 ft

PHYSICAL SPECIFICATION

Dimensions	76 × 55 × 0.37 mm / 2.99 × 2.17 × 0.015 in
Tag Materials	Special polymer designed for high temperatures
Attachment	Screws or pop rivets through Ø5 mm holes
Weight	1.5 g
Amount in Box	200 pcs
Delivery Format	Single

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
Peak Temperature (168h)	+180°C / +356°F
Peak Temperature (3h)	+230°C / +446°F
Peak Temperature (10min)	+260°C / +500°F
IP Classification	IP68
Chemical Resistance	168h salt water (10%), motor oil, sulfuric acid (10%); 2h NaOH (10%); acetone wipe

FEATURE HIGHLIGHTS

- Survives peak temperature up to 260°C / 500°F for 10 minutes
- Alien Higgs 9 IC with 688-bit User Memory
- Read range up to 10 m / 33 ft (2W ERP)
- IP68 waterproof – chemical resistant to acids, motor oil and NaOH
- Screw/rivet attachment via Ø5 mm holes – flag form factor
- Designed for single-use automotive paint shop lifecycle

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag