

Confidex Ironside Classic RFID Tag

The most durable RFID tag for challenging industrial asset management. SAE AS5678 compliant, IP68-rated and built from high-quality engineering plastics with thermoplastic elastomer surface, delivering read ranges up to 15 m on metal.



RFID SPECIFICATION

Protocol	UHF RFID / EPCglobal Gen2v2 (ISO 18000-6C)
IC Options	Impinj M4QT / M4E / MR6-P
Operating Frequency	860–960 MHz (Global)
Memory (M4QT)	EPC 128 bit; User 512 bit; TID 96 bit
Memory (M4E)	EPC 496 bit; User 128 bit; TID 96 bit
Read Range – ETSI on metal	Up to 15 m / 50 ft
Read Range – FCC on metal	Up to 15 m / 50 ft
Read Range – Global on metal (ETSI)	Up to 9 m / 30 ft

PHYSICAL SPECIFICATION

Dimensions	51.5 × 47.5 × 10 mm / 2.03 × 1.87 × 0.39 in
Tag Materials	High quality engineering plastics; surface thermoplastic elastomer
Standard Compliance	SAE AS5678
Weight	22 g
Amount in Box	500 pcs
Delivery Format	Single
Attachment Methods	3M 300LSE adhesive, structural adhesive, M4 screws, pop rivets, welding bracket

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C / -40°F to +185°F
Ambient Temperature	-55°C (3h) to +105°C / -67°F to +221°F
Peak Temperature	+125°C / +257°F for 1 hour
IP Classification	IP68
Pressure Resistance	170 kPa for 10 min
Vibration Resistance	JESD22-B103B service condition 2; RTCA DO-160 Rev E 8.5
Operational Shock	RTCA DO-160 Rev E 7.2
Chemical Resistance	168h motor oil, salt water (10%), sulfuric acid (10%); 24h NaOH (10%)

FEATURE HIGHLIGHTS

- SAE AS5678 compliant – certified for industrial asset tracking
- IC options: Impinj M4QT, M4E or MR6-P
- Read range up to 15 m on metal (ETSI/FCC variants)
- IP68, vibration and operational shock resistant (RTCA DO-160)
- Pressure resistance: 170 kPa for 10 min
- Multiple attachment: adhesive, structural adhesive, screws (M4), pop rivets, welding bracket

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag