

Confidex Ironside Micro RFID Tag

Compact square-inch on-metal UHF RFID tag with a 27 × 27 mm footprint. IP68-rated and built from high-quality engineering plastics, suitable for various metal asset tracking applications where space is limited.



RFID SPECIFICATION

Protocol	UHF RFID / ISO 18000-6C / EPCglobal Gen2v2
IC Options	Impinj Monza 4QT / Monza 4E
Operating Frequency	865–928 MHz (Global)
Memory (M4QT)	EPC 128 bit; User 512 bit; TID 96 bit
Memory (M4E)	EPC 496 bit; User 128 bit; TID 96 bit
EPC Content	Unique number encoded
Read Range – ETSI on metal	Up to 5 m / 16 ft
Read Range – FCC on metal	Up to 4 m / 13 ft

PHYSICAL SPECIFICATION

Dimensions	27 × 27 × 5.5 mm / 1.06 × 1.06 × 0.22 in
Tag Materials	High quality engineering plastics
Attachment	Adhesive (3M 300LSE), screws (M3), pop rivets, plastic rivets (3mm)
Weight	4.3 g
Amount in Box	500 pcs
Delivery Format	Single

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
IP Classification	IP68
Chemical Resistance	168h motor oil, salt water (10%); 5h sulfuric acid (10%); 1h NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Square-inch footprint – 27 × 27 × 5.5 mm compact form factor
- IC options: Impinj Monza 4QT / 4E
- Read range up to 5 m (ETSI) / 4 m (FCC) on metal
- IP68 waterproof with chemical resistance
- Multiple attachment: adhesive, screws (M3), pop rivets, plastic rivets
- Polarization at 45° to the Confidex logo

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag