

Confidex Ironside Plate RFID Tag

Robust RAIN RFID tag with aluminum/stainless steel construction and durable laser-engravable surface. Engineered for the most challenging industrial environments, delivering read ranges up to 10 m on metal with IP68 rating.



RFID SPECIFICATION

Protocol	EPCGlobal Class1 Gen2 ISO 18000-6C
Integrated Circuit	NXP UCODE 8
Operating Frequency	865–928 MHz (Global)
EPC Memory	128 bit
TID Memory	96 bit
EPC Content	Unique 96 bit EPC in every tag
Read Range – on metal	Up to 10 m / 33 ft
Read Range – on plastic	Up to 7 m / 23 ft

PHYSICAL SPECIFICATION

Tag Dimensions	108 × 50.8 × 3.7 mm / 4.25 × 2 × 0.15 in
Tag Surface	Top: Aluminum with anti-corrosion coating; Back: Stainless steel
Attachment	3M VHB adhesive (optional), M3 screws or pop rivets (Ø3.3 mm holes)
Weight	68 g
Amount in Box	80 pcs
Delivery Format	Single

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
Ambient Temperature	-35°C to +85°C / -31°F to +185°F
Peak Temperature	+130°C / +266°F for 10 min
Water Resistance	IP68 (tested 5h in 1m deep water)
Washing Resistance	Tolerates industrial washing with standard solvents
Storage Condition	1 year at +20°C / 50% RH
Chemical Resistance	168h motor oil; 24h salt water (10%); 10min sulfuric acid (10%); 10min NaOH (10%)

FEATURE HIGHLIGHTS

- Aluminum top with anti-corrosion coating + stainless steel back
- NXP UCODE 8 IC – EPC 128 bit
- Read range up to 10 m on metal / 7 m on plastic
- IP68 waterproof – industrial washing resistance
- Laser-engravable surface for permanent visual marking
- Multiple attachment: 3M VHB adhesive, M3 screws or pop rivets

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag