

Confidex Steelwave Micro II
RFID Tag

Small-sized on-metal RFID tag with versatile attachment options and unparalleled performance in a compact 38 × 13 mm form factor. IP67-rated, suitable for IT asset tracking, office equipment and inventory management.



RFID SPECIFICATION

Protocol	EPCGlobal Class1 Gen2 ISO 18000-6C
Integrated Circuit	Impinj Monza 4QT (4E upon request)
Operating Frequency	865–928 MHz (Global)
Memory (Monza 4QT)	EPC 128 bit; User 512 bit; TID 96 bit
EPC Content	Unique number encoded
Read Range – on metal	Up to 5 m / 16 ft
Read Range – off metal	Up to 1.5 m / 5 ft

PHYSICAL SPECIFICATION

Dimensions	38 × 13 × 4.5 mm / 1.5 × 0.5 × 0.17 in
Tag Materials	Engineering plastics with synthetic face layer
Adhesive	High performance acrylic adhesive (included)
Attachment Options	Adhesive, hanging with tethering string, cable tie through tag
Weight	2 g
Amount in Box	1000 pcs
Delivery Format	Single

ENVIRONMENTAL RESISTANCE

Operating Temperature	-20°C to +70°C / -4°F to +158°F
IP Classification	IP67
Chemical Resistance	2h salt water (10%), motor oil; short-time sulfuric acid exposure
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Ultra-compact 38 × 13 × 4.5 mm on-metal form factor
- Impinj Monza 4QT IC – EPC 128 bit / User 512 bit
- Read range up to 5 m on metal / 1.5 m off metal
- IP67 rated with acrylic adhesive included
- Multiple attachment: adhesive, tethering string, cable tie
- Applications: IT asset tracking, office equipment, inventory management

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag