

Epozy Printable On-Metal RFID Label 64×6×1 mm

Ultra-slim 64×6×1 mm UHF RFID on-metal label with NXP UCode 8 IC. Ideal for narrow metal assets such as tools, shelving and IT equipment, with read ranges up to 4 m on metal and 4.5 m on plastic.



RFID SPECIFICATION

Protocol	EPC C1G2 (ISO18000-6C)
Integrated Circuit	NXP UCode 8
Operating Frequency	860–960 MHz
EPC Memory	128 bit
TID Memory	96 bit
User Memory	32 bit
Read Range – on metal (FCC)	4 m
Read Range – on plastic (FCC)	4.5 m

PHYSICAL SPECIFICATION

Dimensions	64 × 6 × 1 mm (L×W×T)
Material	PET / Aluminum Foil / Foam
Installation	Adhesive
Supported Printers	SATO CL4NX, Zebra ZT410, Postek TX3r
Package	500 pcs / roll, 76.2 mm / 3" reel core

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C
IP Classification	IP68 (tested 5h at 1m depth)

FEATURE HIGHLIGHTS

- NXP UCode 8 – EPC C1G2 (ISO18000-6C), 860–960 MHz
- Read range up to 4 m on metal / 4.5 m on plastic (FCC)
- IP68 – ultra-slim 64×6 mm for narrow metal surfaces

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag