

Omni-ID Fit 400 HT

Compact High Temperature UHF RFID tag surviving cycling to +235°C with up to 4 m read range. At 13.1×7.8 mm the Fit 400 HT tracks small metal hand tools, IT assets and autoclave/sterilization applications.



RF SPECIFICATION

Radio Protocol	EPC Class 1 Gen2v2
Frequency Range – EU	866–868 MHz
Frequency Range – US	902–928 MHz
IC Type (Chip)	Alien Higgs 3
EPC Memory	96 bits
User Memory	512 bits
Unique TID	64 bits
Read Range – Fixed Reader	Up to 4 m / 13.1 ft
Read Range – Handheld Reader	Up to 2 m / 6.5 ft
Material Compatibility	Metal

PHYSICAL SPECIFICATION

Size	13.1 × 7.8 × 3.1 mm / 0.52 × 0.31 × 0.12 in
Material	Painted Black
Weight	1.6 g
Attachment	Film Adhesive (included)

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-20°C to +85°C
Max Temperature Exposure	-20°C to +235°C
IP Rating	IP68
Certifications	CE, RoHS, Ex; optional ATEX/IECEX, US&Canada C1D1/D2

FEATURE HIGHLIGHTS

- Alien Higgs 3 – EPC Class 1 Gen2v2, EU/US dual frequency
- Read range: 4 m fixed / 2 m handheld – 13.1×7.8×3.1 mm form factor
- Survives cycling to +235°C – IP68, CE, RoHS, Ex certified

PRODUCT GROUP

Category	UHF RFID High Temperature Tag
Product Group	RFID Label / Tag